

RM DS Series



Overview

Featuring a heavy duty, practical design the RM DS series is designed for the demanding vegetation

Capable of mulching dense vegetation and overgrowth the large diameter rotor with anti-shock design protects the assembly from impact caused by contact with hard objects to extend the working life of the machine.

A double skin chassis construction and forged hammer flails come as standard and with high quality build throughout, the RM DS series gives operators unrivaled reliability.

For high intensity operations, downtime is kept to a minimum with rotor bearings easily accessible. Cutting height is also easily adjustable via the rear roller and full length adjustable skid shoes.

With a 470mm fully hydraulic side shift and an adjustable tailgate, operators of the RM DS Series are given the flexibility and practicality they demand.

Features

- **Heavy duty 470mm hydraulic side shift**
- **Adjustable rear tailgate for easy access**
- **Anti-shock rotor with heavy duty forged hammer flails**
- **Adjustable rear roller and full length skids**
- **Double skin chassis and high quality build**

Specification

RM DS Series	RM 260 DS	RM 280 DS	RM 300 DS
HP Requirement	75 - 200 HP	75 - 200 HP	75 - 200 HP
Width	256cm	276cm	296cm
Dimensions	275 x 130 x 95cm	295 x 130 x 95cm	315 x 130 x 95cm
Linkage Type	Cat 2 3-Point	Cat 2 3-Point	Cat 2 3-Point
Hydraulic Side Shift	470mm	470mm	470mm
PTO Speed	540 / 1000rpm	540 / 1000rpm	540 / 1000rpm
Chassis Construction	Double Skin	Double Skin	Double Skin
Number of Flails	24	26	28
Weight	890kg	940kg	985kg

* Other sizes are available on request

Watch the video

